



Product Service

# Attestation of Conformity

No. N8A 111579 0003 Rev. 00

**Holder of Certificate:** **Wuxi Wattsonic Energy Technology Co., Ltd**  
NO. B1-416  
NO. 200 Linghu Road  
Xinwu  
214100 Wuxi  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Converter**  
**HYBRID INVERTER**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 701262104001-00

**Date,** 2021-03-16

( Zhengdong Ma )

Page 1 of 5

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

# Attestation of Conformity

No. N8A 111579 0003 Rev. 00

**Model(s):** **WTS-4KW-3P, WTS-5KW-3P, WTS-6KW-3P,  
WTS-8KW-3P, WTS-10KW-3P, WTS-12KW-3P.**

## Parameters:

Models	WTS-4KW-3P	WTS-5KW-3P	WTS-6KW-3P
PV Port			
D.C. Max. Input Voltage:	1000 Vd.c.	1000 Vd.c.	1000 Vd.c.
D.C. MPPT Voltage Range:	150-850 Vd.c.	150-850 Vd.c.	200-850 Vd.c.
D.C. Max. Input Current:	13/13 Ad.c.	13/13 Ad.c.	13/13 Ad.c.
Isc PV:	18/18 Ad.c.	18/18 Ad.c.	18/18 Ad.c.
Battery Port			
Battery Voltage Range:	180-750 Vd.c.	180-750 Vd.c.	180-750 Vd.c.
Battery Max. Charge/Discharge Current:	25 Ad.c.	25 Ad.c.	25 Ad.c.
Battery Type:	Li-Ion	Li-Ion	Li-Ion
AC Input Port			
AC Input Nominal Voltage:	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V
AC Input Nominal Frequency:	50/60 Hz	50/60 Hz	50/60 Hz
AC Input Max. Current:	11.6 Aa.c.	14.5 Aa.c.	17.4 Aa.c.
AC Input Max. Apparent Power:	8000 VA	10000 VA	12000 VA



# Attestation of Conformity

No. N8A 111579 0003 Rev. 00

Models	WTS-4KW-3P	WTS-5KW-3P	WTS-6KW-3P
<b>AC Output Port</b>			
A.C. Output Nominal Voltage:	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V
A.C. Output Nominal Frequency:	50/60 Hz	50/60 Hz	50/60 Hz
A.C. Output Rated Power:	4000 W	5000 W	6000 W
A.C. Output Rated Apparent Power:	4000 VA	5000 VA	6000 VA
A.C. Output Max. Apparent Power:	4400 VA	5500 VA	6600 VA
A.C. Output Rated Current:	5.8 Aa.c.	7.3 Aa.c.	8.7 Aa.c.
A.C. Output Max. Current:	6.7 Aa.c.	8.3 Aa.c.	10 Aa.c.
Power Factor:	0.8leading... 0.8lagging	0.8leading... 0.8lagging	0.8leading... 0.8lagging
<b>Back-up Output Port</b>			
Back-up Output Nominal Voltage:	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V
Back-up Output Nominal Frequency:	50/60 Hz	50/60 Hz	50/60 Hz
Back-up Output Rated Power:	4000 W	5000 W	6000 W
Back-up Output Rated Apparent Power:	4000 VA	5000 VA	6000 VA
Back-up Output Max. Apparent Power:	4400 VA	5500 VA	6600 VA
<b>General Data</b>			
Operating Attitude:	3000 m		
Protective Class:	I		
Ingress Protection:	IP65		
Overvoltage Category:	II(DC), III(AC)		
Operating Temperature Range:	-30°C ... +60°C		
Inverter Topology:	Non-isolated		



# Attestation of Conformity

No. N8A 111579 0003 Rev. 00

Models	WTS-8KW-3P	WTS-10KW-3P	WTS-12KW-3P
<b>PV Port</b>			
D.C. Max. Input Voltage:	1000 Vd.c.	1000 Vd.c.	1000 Vd.c.
D.C. MPPT Voltage Range:	200-850 Vd.c.	200-850 Vd.c.	200-850 Vd.c.
D.C. Max. Input Current:	13/13 Ad.c.	13/13 Ad.c.	13/13 Ad.c.
Isc PV:	18/18 Ad.c.	18/18 Ad.c.	18/18 Ad.c.
<b>Battery Port</b>			
Battery Voltage Range:	180-750 Vd.c.	180-750 Vd.c.	180-750 Vd.c.
Battery Max. Charge/Discharge Current:	25 Ad.c.	25 Ad.c.	25 Ad.c.
Battery Type:	Li-Ion	Li-Ion	Li-Ion
<b>AC Input Port</b>			
AC Input Nominal Voltage:	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V
AC Input Nominal Frequency:	50/60 Hz	50/60 Hz	50/60 Hz
AC Input Max. Current:	23.2 Aa.c.	23.9 Aa.c.	23.9 Aa.c.
AC Input Max. Apparent Power:	16000 VA	16500 VA	16500 VA
<b>AC Output Port</b>			
A.C. Output Nominal Voltage:	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V
A.C. Output Nominal Frequency:	50/60 Hz	50/60 Hz	50/60 Hz
A.C. Output Rated Power:	8000 W	10000 W	12000 W
A.C. Output Rated Apparent Power:	8000 VA	10000 VA	12000 VA
A.C. Output Max. Apparent Power:	8800 VA	11000 VA	13200 VA
A.C. Output Rated Current:	11.6 Aa.c.	14.5 Aa.c.	17.4 Aa.c.
A.C. Output Max. Current:	13.3 Aa.c.	16.5 Aa.c.	20 Aa.c.
Power Factor:	0.8 leading... 0.8 lagging	0.8 leading... lagging	0.8 leading... lagging



Product Service

# Attestation of Conformity

No. N8A 111579 0003 Rev. 00

Models	WTS-8KW-3P	WTS-10KW-3P	WTS-12KW-3P
Back-up Output Port			
Back-up Output Nominal Voltage:	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V	3/N/PE~ 380/400 V
Back-up Output Nominal Frequency:	50/60 Hz	50/60 Hz	50/60 Hz
Back-up Output Rated Power:	8000 W	10000 W	12000 W
Back-up Output Rated Apparent Power:	8000 VA	10000 VA	12000 VA
Back-up Output Max. Apparent Power:	8800 VA	11000 VA	13200 VA
General Data			
Operating Attitude:	3000 m		
Protective Class:	I		
Ingress Protection:	IP65		
Overvoltage Category:	II(DC), III(AC)		
Operating Temperature Range:	-30°C ... +60°C		
Inverter Topology:	Non-isolated		

**Tested according to:**

EN 62109-1:2010  
EN 62109-2:2011